



**Guardian FireShield™**

← 7 1/2" deep at faceplate →

↑ 15 5/8" tall ↓



**Guardian FireShield™**

diameter

**Unit weight:**

7.4 lbs. (including 5 lbs. dry-chem)

**Unit dimensions:**

4 3/8" diameter tank, 15 5/8" tall, 7 1/2" deep at faceplate

**Packaged weight:**

8.4 lbs.

**Packaged dimensions:**

8 1/16" wide x 9 1/2" deep x 17 1/2" tall

**Tank Pressure:**

175 psi

**Activation temperature rating:**

135°F = 57°C

**Effective Temperature Range:**

-45°C (-49°F) to 57°C (135°F)

**Single unit tested suppression coverage (at 8' ceiling height):**

16' x 16' room = 256 sq. ft.

**Product life span:**

5 years

**Battery (for LED low-pressure indication):**

9V

**Certifications:**

**Glass Heat Break V2703** - UL VNIV.EX5170, VFJV.MS26601, MEA (#62-99-E) and CSFM (#7690-0531-112)

**ABC Dry Chemical Agent ABCP** - U.L.C. Classified (Siliconized Mono-Ammonium Phosphate 56%/Sulfate Base) Model #750 CAN/ULC S 514 M88

**Flame Retardant Plastics** - UL E138590

**Sealant LOCTITE 567** - UL MH8007